

REV CHANGE DESCRIPTION MOD.BY CK1 CK2 DATE

SPECIAL FOR D902

NOTES:

1. HOUSING FOR KUBOTA **ENGINES D902**

930100-02 SAE "B" 2-BOLT MOUNT 4.00 DIA PUMP PILOT (2) 1/2-13 TAPPED HOLES EQ. SPACED ON 5.75 B.C.

IMPORTANT INSTALLATION NOTE!!!!!

IMPROPER INSTALLATION OF HUB COULD CAUSE PREMATURE WEAR AND OR FAILURE.

IF YOU HAVE QUESTIONS CONCERNING LOCATION OF METAL HUB ON PUMP SHAFT PLEASE CONTACT DISTRIBUTOR OR FACTORY FOR FURTHER INFORMATION

BOTH HUB SET SCREWS MUST BE PROPERLY TORQUED TO 25 FT.LBS. USING TORQUE WRENCH. PLEASE CONTACT DISTRIBUTOR OR FACTORY FOR ANY FURTHER QUESTIONS.

NOTE: REMOVE HUB FROM ASS'Y, PRESET HUB ON SHAFT AS SHOWN. TORQUE BOTH SET SCREWS TO 25 FT.LBS. USING TORQUE WRENCH. SHAFT SHOULD HAVE A MINIMUM OF 3/4" OF ENGAGEMENT IF NOT CONTACT FACTORY FOR RECOMMENDATIONS (231) 879-3372 TO GET HUB PRESET USE THIS EQUATION:

PERFORM CALCULATION BELOW: - SHAFT LENGTH - HUB PRESET 1.55

2.02 -

- 3.75


IF YOUR ANSWER IS (+) SHAFT IS INSIDE OF HUB, IF YOUR ANSWER IS (-) SHAFT STICKS OUT OF HUB. (SEE BOXES)

THIS DRAWING IS THE PROPERTY OF HAYES MFG, INC. AND IS LOANED SUBJECT TO THE CONDITION THAT IT SHALL DO NOT BE REPRODUCED. COPIED, LOANED OR OTHERWISE DISPOSED OF, DIRECTLY OR INDIRECTLY. IT SHALL BE USED AS A MEANS OF REFERENCE TO WORK PURNISHED BY THIS COMPANY ONLY AND IS NOT TO BE SUBMITTED TO OUTSIDE PARTIES FOR EXAMINATION WITHOUT OUR CONSENT.

NOTE: THIS STEP IS IMPORTANT TO ENSURE FULL SHAFT ENGAGEMENT.

TORQUE M8x1.25 BOLTS

13-15 FT.LBS



5 930100-02 HOUSING 4 930112 BOLT KIT 3 SD200X5/16X1/2 5/16 X 1/2 SPRING DOWEL 2 HB1-07 HEX~FLX HUB 1 B-SMN HEX~FLX FLYWHEEL PLATE	200	DADT NUMBER	DECODIDATION	OT/
4 930112 BOLT KIT	1	B-SMN	HEX~FLX FLYWHEEL PLATE	1
4 930112 BOLT KIT	2	HB1-07	HEX~FLX HUB	1
	3	SD200X5/16X1/2	5/16 X 1/2 SPRING DOWEL	2
5 930100-02 HOUSING	4	930112	BOLT KIT	1
	5	930100-02	HOUSING	1

ı		1	B-SMN		HEX~FLX FLYW	HEEL PLATE	1	
	SYMBOLS	DET.	PART NUMBER		DESCRIPTION		QTY.	
	## PARALLELISM © CONCENTRICITY TRUE POSITION O ROUNDNESS CIRCULAR RUN OUT TOTAL RUN OUT CYLINDRICITY	DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE SPECIFIED 125 MAXIMUM ANGLE ±1/2* FRACTION ±1/32 DECIMAL .00 ±.01 .000 ±.01		TITLE KUBOTA MINI HEX~FLX COUPLING ASS'Y MATURACTURING INC. ®				
	CLASS	AKE: X	.0000 ±.0005	DRAWN BY	DATE	DRAWING NO.		
	KUBOTA Management Mana	#ANE.[A] BUT:		SIETING CHECKED B	04-12-2011 Y SCALE	044-0-HB1-07-	B2	

SHEET OF REV.