


REV	DATE	CHANGE DESCRIPTION	MOD.BY	CK1	CK2
D1	11/29/2004	FIXED PRINT.	ZS	RJH	HM




NOTE: REMOVE HUB FROM ASS'Y, PRESET HUB ON SHAFT & REASSEMBLE USING NUT & BOLT GRADE LOC-TITE ON SET SCREWS. SHAFT SHOULD HAVE A MINIMUM OF 3/4" OF ENGAGEMENT IF NOT CONTACT FACTORY FOR RECOMMENDATIONS. TO GET HUB PRESET USE THIS EQUATION:

EXAMPLE:
2.01 - SHAFT LENGTH = HUB PRESET

IF YOUR ANSWER IS (+) SHAFT IS INSIDE OF HUB, IF YOUR ANSWER IS (-) SHAFT STICKS OUT OF HUB. (SEE BOXES)

THIS DRAWING IS THE PROPERTY OF HAYES MFG. INC. AND IS LOANED SUBJECT TO THE CONDITION THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED OR OTHERWISE DISPOSED OF, DIRECTLY OR INDIRECTLY. IT SHALL BE USED AS A MEANS OF REFERENCE TO WORK FURNISHED BY THIS COMPANY ONLY AND IS NOT TO BE SUBMITTED TO OUTSIDE PARTIES FOR EXAMINATION WITHOUT OUR CONSENT.

NOTE: THIS STEP IS IMPORTANT TO ENSURE FULL SPLINE ENGAGEMENT.



COUPLING ASS'Y #125212

14	123008-G02	PUMP MOUNT PLATE [5]	1
13	801912	GREASE	1
12	PURCHASE	5/16-18 x 5/8" SSSCP	1
11	PURCHASE	5/16-18 x 1/2" SSSCP	1
10	568-143	O-RING (124865)	1
9	568-142	O-RING (124284-11)	1
8	N250	7/16-20 NUT	8
7	HX230	7/16-20 x 1 3/4" HHB	8
6	123000-00	STEEL RIVET	8
5	H62500	NEOPRENE INSERT	8
4	124284-11	EXT SPL HUB [40T16/32\1.00B.250K]	1
3	124865	INT SPL HUB [40T16/32\5.000]	1
2	124657-02	BACKING PLATE	1
1	123243-13	FLYWHEEL PLATE [8\5.000]	1

SYMBOLS	DET.	PART NUMBER	DESCRIPTION	QTY.
FLATNESS STRAIGHTNESS ANGULARITY SQUARENESS PARALLELISM CONCENTRICITY TRUE POSITION ROUNDNESS CIRCULAR RUN OUT TOTAL RUN OUT CYLINDRICITY FINISH	DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE SPECIFIED 12/32 MAXIMUM ANGLE ±1/2° FRACTION ±1/32 DECIMAL .00 ±.01 .000 ±.005 .0000 ±.0005		HAYES MANUFACTURING INC. ® TITLE FLYWHEEL COUPLING ASS'Y MATERIAL	
- UNLESS OTHERWISE SPECIFIED - REMOVE FIRST THREAD ON ALL TAPPED HOLES BREAK ALL SHARP CORNERS .010 TO .020 STAMP OR MARK DRAWING NO.	DRAWN BY SIETING CHECKED BY RJH	DATE 10-28-98 SCALE	DRAWING NO. 123933 SHEET OF REV.	