



NOTES:

1. HOUSING FOR KUBOTA ENGINES D902
2. USE FURNISHED COUPLING GREASE ON BOTH MALE AND FEMALE SPLINE.

SPECIAL FOR D902

NOTES:

1. LIGHTLY GREASE INTERNAL AND EXTERNAL AREA OF SPLINE AT ASSEMBLY USING COUPLING GREASE (OVER GREASING COULD CAUSE A HYDRAULIC TYPE LIFT ON SEALS). GREASE BEARING HOUSING UNTIL PIN EXTENDS FROM PRESSURE RELIEF VALVE (LOCATED 180° FROM GREASE ZERK).
2. USE OF AN UNLEADED EXTREME PRESSURE LITHIUM GREASE, WITH NLGI NO.2 GRADE IS RECOMMENDED. RUN TIME BETWEEN GREASINGS NOT TO EXCEED 2,000 HOURS.
3. **WARNING!!!** INJURY OR DEATH FROM A ROTATING STUB SHAFT CAN OCCUR IF A CONDITION EXISTS WHICH WOULD CAUSE THE SHAFT TO BREAK OR COME APART FROM ANY PART OF THE ASSEMBLY. DEPENDING UPON THE APPLICATION (FOR EXAMPLE, FAN, PULLEY, SHEAVE, ETC.), THE AREA AROUND THE STUB SHAFT MUST BE SUFFICIENTLY GUARDED SO THAT IN THE EVENT OF FAILURE, THE GUARD WILL CONTAIN ANY AIRBORNE PARTS.

SPLINE DATA:
14 TOOTH
12/24 D.P.
30° P.A.

SUB ASS'Y #125714

COUPLING ASS'Y #127772

KUBOTA STARTER PLATE
#1G960-04621

THIS DRAWING IS THE PROPERTY OF HAYES MFG. INC. AND IS LOANED SUBJECT TO THE CONDITION THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED OR OTHERWISE DISPOSED OF, DIRECTLY OR INDIRECTLY. IT SHALL BE USED AS A MEANS OF REFERENCE TO WORK FURNISHED BY THIS COMPANY ONLY AND IS NOT TO BE SUBMITTED TO OUTSIDE PARTIES FOR EXAMINATION WITHOUT OUR CONSENT.

REV	DATE	CHANGE DESCRIPTION	MOD. BY	CK1	CK2
C	06/08/2016	CHANGED SEAL	BSL	HM	JM

22	930115-01	HOUSING	1
21	972000	BOLT KIT (PRE-ASSEMBLED)	1
20	SD200	SD200x5/16X1/2	2
19	BOLT	1/2-13x1-1/8 SHCS D	4
18	132015	SEAL	1
17	VS-032	V-RING	1
16	1093K11	RELIEF VALVE	1
15	609000	GREASE ZERK	1
14	125294	5/8-11 HHB	1
13	125713	SPLINED SHAFT	1
12	RR-314	SNAP RING	1
11	600000	GREASE ZERK	1
10	125007	BEARING HOUSING	1
9	5208WD	DOUBLE BEARING	1
8	208KD	BEARING	1
7	801912	GREASE	1
6	R-0017-02	GREASE PLUG	1
5	HX300	SPEC. 5/16-24x5/8 HHB Y D	5
4	123729-01	THREADED BUSHING	5
3	H52500	NEOPRENE INSERT	5
2	127773	COUP HUB [14T 16/32\4.125]	1
1	127623	FLYWHEEL PLATE	1

SYMBOLS	DET.	PART NUMBER	DESCRIPTION	QTY.
——— FLATNESS ——— STRAIGHTNESS ——— ANGULARITY ⊥ PERPENDICULARITY // PARALLELISM @ CONCENTRICITY ⊕ TRUE POSITION ○ ROUNDNESS ↗ CIRCULAR RUN OUT ↖ TOTAL RUN OUT / CYLINDRICITY ✓ FINISH	DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE SPECIFIED .125 MAXIMUM ANGLE ±1/2° FRACTION ±1/32 DECIMAL .00 ±.01 .000 ±.005 .0000 ±.0005	<input checked="" type="checkbox"/> MAKE <input type="checkbox"/> BUY	 TITLE KUBOTA MINI SERIES BEARING SUPPORTED STUB SHAFT ASSY MATERIAL	
CLASS BS ASSY DESCRIPTION KB902,1-7/16,5	DRAWN BY SIETING CHECKED BY R/JH	DATE 09-18-06 SCALE	DRAWING NO. 902550 SHEET OF REV.	