


REV	DATE	CHANGE DESCRIPTION	MOD. BY	CK1	CK2
H1	05/06/2009	UPDATED GREASE NOTE	ZS	RJH	HM



NOTE:
THIS ASSEMBLY WORKS WITH:
FLYWHEELS C-9(16614-25112)
C-8(16692-25113)
& STARTER PLATE E-1(16241-04621)

ASSEMBLY NOTE:
 ENSURE THAT THE GREASE ZERT AND RELIEF VALVE ARE LOCATED HORIZONTAL WHEN MOUNTING ON TO PUMP MOUNT PLATE.

REPLACES: 952085

QTY.	PART NUMBER	DESCRIPTION
1	20 952111	BOLT KIT
2	19 PURCHASE	5/16x1/2 DOWEL
1	18 952089-01	HOUSING
1	17 1093K11	RELIEF VALVE
4	16 740000	1/2-13-1-1/8 SHCS
1	15 125710	SPLINED SHAFT
1	14 CRW1-R-15830	SEAL
1	13 RR-314	SPIROLOX SNAP RING
2	12 600000	GREASE ZERT
1	11 5208WD	DOUBLE BEARING
1	10 125007	BEARING HOUSING
1	9 208P	BEARING
1	8 VS-032	V-RING
1	7 801912	GREASE
1	6 R-0017-01	GREASE PLUG
8	5 H52500	NEOPRENE INSERT
8	4 HX300	BOLT
8	3 123729-01	THREADED BUSHING
1	2 126105	COUPLING HUB
1	1 124118-06	FLYWHEEL PLATE

NOTES:

1. LIGHTLY GREASE INTERNAL AND EXTERNAL AREA OF SPLINE AT ASSEMBLY USING SUPPLIED COUPLING GREASE (OVER GREASING COULD CAUSE A HYDRAULIC TYPE LIFT ON SEALS).
2. **AT ASSEMBLY GREASE BEARING HOUSING UNTIL PIN EXTENDS FROM PRESSURE RELIEF VALVE (LOCATED 180° FROM GREASE ZERT).** USE OF AN UNLEADED EXTREME PRESSURE LITHIUM GREASE, WITH NLGI NO.2 GRADE IS RECOMMENDED. RUN TIME BETWEEN GREASINGS NOT TO EXCEED 2,000 HOURS.
3. **WARNING!!!** INJURY OR DEATH FROM A ROTATING STUB SHAFT CAN OCCUR IF A CONDITION EXISTS WHICH WOULD CAUSE THE SHAFT TO BREAK OR COME APART FROM ANY PART OF THE ASSEMBLY. DEPENDING UPON THE APPLICATION (FOR EXAMPLE, FAN, PULLEY, SHEAVE, ETC.), THE AREA AROUND THE STUB SHAFT MUST BE SUFFICIENTLY GUARDED SO THAT IN THE EVENT OF FAILURE, THE GUARD WILL CONTAIN ANY AIRBORNE PARTS.

4. HOUSING FOR KUBOTA ENGINES D-905, D1005-B, D1105-B, V1205-B, V1305-B AND V1505-B

BEARING SUPPORTED
 STUB SHAFT SUB-ASS'Y
 #125711

COUPLING ASS'Y
 125747

THIS DRAWING IS THE PROPERTY OF HAYES MFG. INC. AND IS LOANED SUBJECT TO THE CONDITION THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED OR OTHERWISE DISPOSED OF, DIRECTLY OR INDIRECTLY. IT SHALL BE USED AS A MEANS OF REFERENCE TO WORK FURNISHED BY THIS COMPANY ONLY AND IS NOT TO BE SUBMITTED TO OUTSIDE PARTIES FOR EXAMINATION WITHOUT OUR CONSENT.

SYMBOLS	DET.	PART NUMBER	DESCRIPTION	QTY.
▭ FLATNESS ▭ STRAIGHTNESS ▭ ANGULARITY ⊥ PERPENDICULARITY ▭ PARALLELISM ⊙ CONCENTRICITY ⊕ TRUE POSITION ○ ROUNDNESS ⊙ CIRCULAR RUN OUT ⊙ TOTAL RUN OUT ⊙ CYLINDRICITY ▭ FINISH	DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE SPECIFIED 125 MAXIMUM ANGLE ±1/2° FRACTION ±1/32 DECIMAL .00 ±.01 .000 ±.005 .0000 ±.0005			
CLASS MAKE: <input type="checkbox"/> BUY: <input type="checkbox"/>		TITLE KUBOTA -05 BEARING STUB SHAFT ASS'Y		
DESCRIPTION		DRAWN BY HAVEMAN	DATE 8-9-00	DRAWING NO. 952127
		CHECKED BY	SCALE	SHEET OF REV.