


REV	DATE	CHANGE DESCRIPTION	MOD.BY	CK1	CK2
C	06/08/2016	CHANGED SEAL	BSL	HM	JM



NOTE:
THIS ASSEMBLY WORKS WITH:
FLYWHEELS C-9(16614-25112)
C-8(16692-25113)
& STARTER PLATE E-1(16241-04621)

ASSEMBLY NOTE:

ENSURE THAT THE GREASE ZERK
AND RELIEF VALVE ARE LOCATED
HORIZONTAL WHEN MOUNTING ON
TO PUMP MOUNT PLATE.

NOTES:

1. LIGHTLY GREASE INTERNAL AND EXTERNAL AREA OF SPLINE AT ASSEMBLY USING COUPLING GREASE (OVER GREASING COULD CAUSE A HYDRAULIC TYPE LIFT ON SEALS). GREASE BEARING HOUSING UNTIL PIN EXTENDS FROM PRESSURE RELIEF VALVE (LOCATED 180° FROM GREASE ZERK).
2. USE OF AN UNLEADED EXTREME PRESSURE LITHIUM GREASE, WITH NLGI NO.2 GRADE IS RECOMMENDED. RUN TIME BETWEEN GREASINGS NOT TO EXCEED 2,000 HOURS.
3. **WARNING!!!** INJURY OR DEATH FROM A ROTATING STUB SHAFT CAN OCCUR IF A CONDITION EXISTS WHICH WOULD CAUSE THE SHAFT TO BREAK OR COME APART FROM ANY PART OF THE ASSEMBLY. DEPENDING UPON THE APPLICATION (FOR EXAMPLE, FAN, PULLEY, SHEAVE, ETC.), THE AREA AROUND THE STUB SHAFT MUST BE SUFFICIENTLY GUARDED SO THAT IN THE EVENT OF FAILURE, THE GUARD WILL CONTAIN ANY AIRBORNE PARTS.
4. HOUSING FOR KUBOTA ENGINES D-905, D1005-B, D1105-B, V1205-B, V1305-B AND V1505-B

**BEARING SUPPORTED
STUB SHAFT SUB-ASS'Y
#127838**

**COUPLING ASS'Y
125747**

20	952111	BOLT KIT (PRE-ASSEMBLED)	1
19	DOWEL	SD200x5/16x1/2 DOWEL PIN	2
18	952066-01	HOUSING	1
17	1093K11	RELIEF VALVE	1
16	BOLT	1/2-13x1-1/8 SHCS D	4
15	127837	SPLINED SHAFT	1
14	132015	SEAL	1
13	RR-314	SPIROLOX SNAP RING	1
12	600000	GREASE ZERK	2
11	5208WD	DOUBLE BEARING	1
10	125007	BEARING HOUSING	1
9	208KD	BEARING	1
8	VS-032	V-RING	1
7	801912	GREASE	1
6	R-0017-01	GREASE PLUG	1
5	H52500	NEOPRENE INSERT	8
4	HX300	SPEC. 5/16-24x5/8 HHB Y D	8
3	123729-01	THREADED BUSHING	8
2	126105	COUPLING HUB	1
1	124118-06	FLYWHEEL PLATE	1

THIS DRAWING IS THE PROPERTY OF HAYES MFG. INC. AND IS LOANED SUBJECT TO THE CONDITION THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED OR OTHERWISE DISPOSED OF, DIRECTLY OR INDIRECTLY. IT SHALL BE USED AS A MEANS OF REFERENCE TO WORK FURNISHED BY THIS COMPANY ONLY AND IS NOT TO BE SUBMITTED TO OUTSIDE PARTIES FOR EXAMINATION WITHOUT OUR CONSENT.

SYMBOLS	DET.	PART NUMBER	DESCRIPTION	QTY.
FLATNESS STRAIGHTNESS ANGULARITY PERPENDICULARITY PARALLELISM CONCENTRICITY TRUE POSITION ROUNDNESS CIRCULAR RUN OUT TOTAL RUN OUT CYLINDRICITY FINISH	DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE SPECIFIED .125" MAXIMUM ANGLE ±1/2° FRACTION ±1/32 DECIMAL .00 ±.01 .000 ±.005 .0000 ±.0005	MAKE: <input checked="" type="checkbox"/> BUY: <input type="checkbox"/>	HAYES MANUFACTURING INC. ® TITLE KUBOTA -05 BEARING STUB SHAFT ASSY MATERIAL	
CLASS BS ASSY DESCRIPTION KB05,1-1/2,4,LNG	DRAWN BY SIETING CHECKED BY	DATE 02-17-05 SCALE	DRAWING NO. 952173 SHEET OF REV.	