REV	DATE	CHANGE DESCRIPTION	MOD.BY	CK1	CK2



NOTE:
THIS ASSEMBLY WORKS WITH:
FLYWHEELS C–9(16614–25112)
C–8(16692–25113)
& STARTER PLATE E–1(16241–04621)

ASSEMBLY NOTE:

ENSURE THAT THE GREASE ZERT AND RELIEF VALVE ARE LOCATED HORIZONTAL WHEN MOUNTING ON TO PUMP MOUNT PLATE.

BEARING SUPPORTED
STUB SHAFT SUB–ASS'Y
132xxx

COUPLING ASS'Y
125747

22	952111	BOLT KIT (PRE–ASSEMBLED)	1
21	DOWEL	SD200x5/16x1/2 DOWEL PIN	2
20	952066–01	HOUSING	1
19	BOLT	1/2–13x1–1/8 SHCS D	4
18	609000	GREASE ZERK	1
17	132XXX	SPECIAL HHB	1
16	1093K11	RELIEF VALVE	1
15	132xxx	SPLINED SHAFT	1
14	15830	SEAL	1
13	RR–314	SPIROLOX SNAP RING	1
12	600000	GREASE ZERT	2
11	5208WD	DOUBLE BEARING	1
10	125007	BEARING HOUSING	1
9	208KD	BEARING	1
8	VS–032	V–RING	1
7	801912	GREASE	1
6	R–0017–01	GREASE PLUG	1
5	H52500	NEOPRENE INSERT	8
4	HX300	SPEC 5/16–24x5/8 HHB Y D	8
3	123729–01	THREADED BUSHING	8
2	126105	COUPLING HUB	1
1	124118–06	FLYWHEEL PLATE	1

NOTES:

1. LIGHTLY GREASE INTERNAL AND EXTERNAL AREA OF SPLINE AT ASSEMBLY USING SUPPLIED COUPLING GREASE (OVER GREASING COULD CAUSE A HYDRAULIC TYPE LIFT ON SEALS).

2. GREASE BEARING HOUSING UNTIL PIN EXTENDS FROM PRESSURE RELIEF VALVE (LOCATED 180° FROM GREASE ZERT). USE OF AN UNLEADED EXTREME PRESSURE LITHIUM GREASE, WITH NLGI NO.2 GRADE IS RECOMMENDED. RUN TIME BETWEEN GREASINGS NOT TO EXCEED 2,000 HOURS.

3. WARNING!!! INJURY OR DEATH FROM A ROTATING STUB SHAFT CAN OCCUR IF A CONDITION EXISTS WHICH WOULD CAUSE THE SHAFT TO BREAK OR COME APART FROM ANY PART OF THE ASSEMBLY. DEPENDING UPON THE APPLICATION (FOR EXAMPLE, FAN, PULLEY, SHEAVE, ETC.), THE AREA AROUND THE STUB SHAFT MUST BE SUFFICIENTLY GUARDED SO THAT IN THE EVENT OF FAILURE, THE GUARD WILL CONTAIN ANY AIRBORNE PARTS.

4. HOUSING FOR KUBOTA ENGINES D–905, D1005–B, D1105–B, V1205–B, V1305–B AND V1505–B

THIS DRAWING IS THE PROPERTY OF HAYES MFG. INC. AND IS LOANED SUBJECT TO THE CONDITION THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED OR OTHERWISE DISPOSED OF, DIRECTLY OR INDIRECTLY. IT SHALL BE USED AS A MEANS OF REFERENCE TO WORK FURNISHED BY THIS COMPANY ONLY AND IS NOT TO BE SUBMITTED TO OUTSIDE PARTIES FOR EXAMINATION WITHOUT OUR CONSENT.

SYMBOLS: FLATNESS, STRAIGHTNESS, ANGULARITY, PERPENDICULARITY, PARALLELISM, CONCENTRICITY, TRUE POSITION, ROUNDNESS, CIRCULAR RUN OUT, TOTAL RUN OUT, CYLINDRICITY, FINISH

DET. | PART NUMBER | DESCRIPTION | QTY.

DO NOT SCALE DRAWING
TOLERANCES UNLESS OTHERWISE SPECIFIED
125 MAXIMUM
ANGLE ±1/2°
FRACTION ±1/32
DECIMAL
.00 ±.01
.000 ±.005
.0000 ±.0005

HAYES MANUFACTURING INC. ®

TITLE: KUBOTA 05 BEARING SUPPORTED STUB SHAFT KIT

MATERIAL

CLASS: BS ASSY | MAKE: [X] BUY: [ ]

DESCRIPTION: KB05,1–1/8x1/4

DRAWN BY: SIETING | DATE: 11–24–2015

CHECKED BY | SCALE

DRAWING NO. 952255

SHEET OF REV.

COPYRIGHT ©2000–2015 by Hayes Manufacturing, Inc. All rights reserved.

12/7/2015 3:58:19 PM