


REV	DATE	CHANGE DESCRIPTION	MOD.BY	CK1	CK2



NOTE:

- HOUSING FOR KUBOTA ENGINES
D-905, D1005-B, D1105-B,
V1205-B, V1305-B AND V1505-B
- USE FURNISHED COUPLING GREASE
ON BOTH MALE AND FEMALE SPLINE.

**COUPLING INTENDED FOR SHORT
3/4" SHAFTS.**

UP TO 50 H.P.

14	952111	BOLT KIT	1
13	PURCHASE	5/16 DIA x 1/2 DOWEL PIN	2
12	952088-01	HOUSING	1
11	801912	GREASE	1
10	568-143	O-RING (124282-02)	1
9	568-142	O-RING (126947-07)	1
8	PURCHASE	5/16-18 x 5/8 SET SCREW	1
7	PURCHASE	5/16-18 x 3/4 SET SCREW	1
6	HX300	SPECIAL 5/16-24 HHB	6
5	H52500	NEOPRENE INSERT	6
4	123729-01	THREADED BUSHING	6
3	126947-07	EXTERNAL SPLINED ADAPTER	1
2	124282-02	INTERNAL SPLINED HUB	1
1	124118-08	FLYWHEEL PLATE	1


COUPLING ASS'Y #126948

NOTE: REMOVE HUB FROM ASS'Y, PRESET HUB ON SHAFT & REASSEMBLE USING NUT & BOLT GRADE LOC-TITE ON SET SCREWS. SHAFT SHOULD HAVE A MINIMUM OF 3/4" OF ENGAGEMENT IF NOT CONTACT FACTORY FOR RECOMMENDATIONS. TO GET HUB PRESET USE THIS EQUATION:

EXAMPLE:
1.78 - SHAFT LENGTH = HUB PRESET

IF YOUR ANSWER IS (+) SHAFT IS INSIDE OF HUB, IF YOUR ANSWER IS (-) SHAFT STICKS OUT OF HUB. (SEE BOXES)

NOTE: THIS STEP IS IMPORTANT TO ENSURE FULL SPLINE ENGAGEMENT.



THIS DRAWING IS THE PROPERTY OF HAYES MFG. INC. AND IS LOANED SUBJECT TO THE CONDITION THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED OR OTHERWISE DISPOSED OF, DIRECTLY OR INDIRECTLY. IT SHALL BE USED AS A MEANS OF REFERENCE TO WORK FURNISHED BY THIS COMPANY ONLY AND IS NOT TO BE SUBMITTED TO OUTSIDE PARTIES FOR EXAMINATION WITHOUT OUR CONSENT.

SYMBOLS	DET.	PART NUMBER	DESCRIPTION	QTY.
FLATNESS STRAIGHTNESS ANGULARITY SQUARENESS PARALLELISM CONCENTRICITY TRUE POSITION ROUNDNESS CIRCULAR RUN OUT TOTAL RUN OUT CYLINDRICITY FINISH	DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE SPECIFIED 12/32 MAXIMUM ANGLE ±1/2° FRACTION ±1/32 DECIMAL .00 ±.01 .000 ±.005 .0000 ±.0005		HAYES MANUFACTURING INC. ® TITLE KUBOTA -05 SERIES HOUSING ASS'Y MATERIAL	
- UNLESS OTHERWISE SPECIFIED - REMOVE FIRST THREAD ON ALL TAPPED HOLES BREAK ALL SHARP CORNERS .010 TO .020 STAMP OR MARK DRAWING NO.	DRAWN BY SIETING CHECKED BY RJH	DATE 04-18-05 SCALE	DRAWING NO. 990120 SHEET OF REV.	