

C-010 S.A.E. 10 FIBERGLASS REINFORCED NYLON DRIVE PLATE (8) .416 HOLES EQ. SPACED ON A 11.625 B.C.

"C" SERIES DRIVE

CHANGE DESCRIPTION

REV DATE

MOD.BY CK1 CK2

IMPORTANT INSTALLATION NOTE!!!!!

IMPROPER INSTALLATION OF HUB COULD CAUSE PREMATURE WEAR AND OR FAILURE.

IF YOU HAVE QUESTIONS CONCERNING LOCATION OF METAL HUB ON PUMP SHAFT PLEASE CONTACT DISTRIBUTOR OR FACTORY FOR FURTHER INFORMATION

BOTH HUB SET SCREWS MUST BE PROPERLY TORQUED TO 25 FT.LBS. USING TORQUE WRENCH. PLEASE CONTACT DISTRIBUTOR OR FACTORY FOR ANY FURTHER QUESTIONS.

"C" SERIES TORQUE RANGE 65-200 HP

	3	123845-	-02	PUM	PUMP MOUNT PLATE					1
	2	HC3-92		C SERIES HEXA			FLX H	UB		1
	1	C-010		SAE 10 HEX~FLX DRIVE PLATE					ATE:	1
SYMBOLS FLATNESS STRAGHTNESS ANGULARITY PARALLELISM OCONCENTRICITY TRUE POSITION O ROUNDRESS CIRCULAR RUN OUT CYLINDRICITY CYLINDRICITY FINISH FINISH	DET.	PART N	JMBER	DES		DESCRIPTION	TION			QTY.
	TOLER	NOT SCALE DRAWING ANCES UNLESS WISE SPECIFIED			H	AY		<u>S_</u>	_	
		MAXIMUM	MANUFACTURING INC. (R)							
	FRAC	GLE ±1/2° CTION ±1/32 DECIMAL	HEX~FLX "C" SERIES 2 PIECE COUPLING							
	.0	00 ±.01 00 ±.005 00 ±.0005	MATERIAL							
CLASS	MAKE:	□ BUY:□	DRAWN BY	1	DATE		DRAWING	NO.		
			LAWSON	9	9-13	-10	010 HC3 03 1		00 0	Vo.
DESCRIPTION			CHECKED B	Y 9	SCALE	,	C-010-HC3-92-			
			RJH				SHEET	OF	REV.	

ENSURE FULL SPLINE ENGAGEMENT.

- 1) PRESET HUB ON SHAFT AS SHOWN.
- 2) IF YOUR PUMP SHAFT VARIES FROM THE DRAWN SHAFT LENGTH, CONTACT FACTORY FOR RECOMMENDATIONS.
- TORQUE BOTH SET SCREWS TO 25 FT.LBS. USING **TORQUE WRENCH.**
- SHAFT SHOULD HAVE FULL SPLINE ENGAGEMENT INTO HUB, IF NOT CONTACT FACTORY FOR RECOMMENDATIONS (231) 879-3372.

THIS DRAWING IS THE PROPERTY OF HAYES MFG, INC. AND IS LOANED SUBJECT TO THE CONDITION THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED OR OTHERWISE DISPOSED OF, DIRECTLY OR MODIFICATLY, IT SHALL BE USED AS A MEANS OF REFERENCE TO WORK FURNISHED BY THIS COMPANY ONLY AND IS NOT TO BE SUBMITTED TO OUTSIDE PARTIES FOR EXAMINATION WITHOUT OUR CONSENT.

